

CATEGORY 3	MONOHULLS	For Offshore races across open water which is relatively protected or close to shorelines
DATE OF AUDIT ____ / ____ / ____	SAIL NO:	BOAT NAME:

Audit Form valid until 30th June next from the date of this form 30 / 06 / _____, or _____ / _____ / _____ whichever is the earlier. Subject to spot checks Regulation 2.02.2

OWNER DETAILS

OWNER/S NAME:			
OWNER/S YA NO:		OWNER/S CLUB	

BOAT DETAILS

LOA:		DISPL (tonnes):	
HULL MATERIAL:		HULL COLOUR:	
DECK MATERIAL:		DECK COLOUR:	
MAX CREW:		DISTINGUISHING MARKS:	
RMS (MARITIME) HULL REGISTRATION NO:			
RMS (MARITIME) STICKER ISSUED	YES NO		

AMSA REGISTRATION

IF CARRIED, SR 3.25 MARINE RADIO: ACMA Marine Transceiver Licence for HF if carried YES NO Registered call sign HF:		
SR 4.18.1 EPIRBS : Registered YES NO	Number of units for boat:	Number to be hired:

DECLARATION BY OWNER/PERSON IN CHARGE

I have read and understand my obligations as Owner/Person in Charge set out in the YA Special Regulations 2013-2017, in particular 1.02.1, 1.02.2, 1.02.3 Owner's Responsibility, and 2.03.1(a) Function of equipment. I understand that this audit is carried out only as a guide to Owners/Persons in Charge and Race Organising Authorities. An Auditor does not limit or reduce the complete and unlimited responsibility of the Owner/Person in Charge as defined in Special Regulations 1.02.1, 1.02.2, 1.02.3 and 2.03.1.

I undertake that all of the boat's equipment as specified in the YA Special Regulations 2013-2017 will remain on the boat and continue to be in good working order and repair for the duration of each and every race.

Items designated with a shaded box are for the Owner/Person in Charge to ensure compliance when racing and must be initialled by the Owner/Person in Charge.

Signed by Owner/Person in Charge

Date

EQUIPMENT AUDITOR DECLARATION

I have checked the abovementioned boat in accordance with 2.02.2 summarised in the following list, and the items listed were found to be on board, and as per the regulations at the time and date of this Audit. Outstanding items are detailed below.

Audited by (print name):	Signed by Equipment Auditor:
YA Number:	Date:

OUTSTANDING ITEMS - The Equipment listed over the page was complete except for the following items

Equipment Outstanding	Re-Inspected by	YA Auditor No.	Date

CATEGORY 3	MONOHULLS	For Offshore races across open water which is relatively protected or close to shorelines	
DATE OF AUDIT ____/____/____	SAIL NO:	BOAT NAME:	

This Section to be completed and **initialled** by Owner /Person in Charge(O) and Auditor/Inspector (EA)

Reg	Equipment	O	EA	
2.03.1	Equipment functions & adequate for intended use			3.14.1
2.03.2	Ballast & heavy equipment secured			Toe rail minimum height 25mm; Age date before 01/1981; 20mm
3.06.1	(a) 2 exits, 1 forward of mast			3.15.2
	(c) Minimum clearance \varnothing 450mm for Age/ Series Date 07/2010 or later; OR			Toilet, securely fastened or fitted bucket
3.07.1	(d) Circular shape \varnothing 450 mm or 380 mm x 380 mm and area 0.18m ² for Age Date 7/2014 or later			3.16.1
	Hatches or ports open outward if forward of max beam, except if less than 0.071m ²			Bunks, securely fastened, sufficient 50% of crew
3.07.2	(a) i Hatches above water when heeled 90 ^o ;			3.17.1
	(a) iii non complying permitted; size<.071m ²			Cooking stove/ heating appliance safe use in seaway eg. gimballed
3.07.3	(a) iii Kept shut while racing			3.17.2
	(b) Capable of being immediately shut, permanently attached lid			Cooking stove/heating appliance securely fastened, accessible shutoff
3.07.3	Blocking device for low sill companionway			3.17.3
3.07.4	Companionway hatch strong securing arrangement securing hatch in closed position			Gas only permitted for cooking Methylated spirits acceptable for cooking
	(a) (i) Operable from above and below			(a) "REMEMBER to turn off Gas" sign
3.07.4	(ii) Functions independently of blocking devices			(b) Gas detection system if appliance has a pilot light.
	(b) Blocking Devices			3.17.5
3.08.1	(i) retained hatch open or shut			Disposable gas canister to be 225 gms or less
	(ii) secured to boat by lanyard			3.17.6
3.08.2	(iii) permit exit in event of inversion			Gas bottle, spare canisters in separate, ventilated, self draining locker, vapour can escape overboard
	Cockpit strong, self draining at all angles of heel, permanent and integral part of hull			3.17.7
3.08.2	Cockpit essentially watertight			Galley suitable facilities
3.08.3	Bilge pump outlet not connected to cockpit drain			At least 2.5 ltrs water per crew; AND
3.08.4	Bilge pump sole 2% waterline length (LWL) above LWL			3.18.3
3.08.5	Wells-bow, lateral, central, stern, included in cockpit volume			At least 1 water tank securely installed for Age Date 07/1998 or later
3.08.6	Cockpit volume complies with formula			3.18.4
3.08.7	Number of cockpit drains			Emergency drinking water 9 ltrs additional to 3.18.2
	Age/ Series Date before 07/1977; 2 x 25mm			3.19.1
3.09.1	Age/ Series Date after 07/1977; 4 x 20mm			Handholds below decks
	(a) Sea cocks permanently installed.			3.20.3
3.10.1	(b) Plugs for each opening attached/ stowed near			1 manual bilge pump operable with all cockpit seats, hatches & companionways shut
	Sheet winches operator not below deck			3.20.6
3.11.1	Keel stepped mast; heel securely fastened			Bilge pump not to discharge into closed cockpit Bilge pump not connected to cockpit drains
3.12.2	Lifelines taut (50N force applied; \leq 50mm deflection)			3.20.7
3.12.3	(i) Closed bow pulpit forward of forestay OR			a) Bilge pump minimum suction bore 25mm
	(ii) Forward gap open bow pulpit less than 360mm; OR			b) Bilge pump & strum boxes accessible
3.12.3	(iii) Forestay in or forward of gap; gap between forestay & bow pulpit less than 360mm			3.20.8
	(b) Stern pulpit top rail no lower than upper lifelines at forward cockpit station			Pump handle each with lanyard or catch unless permanently fitted
3.12.3	(c) Lifelines, stanchions continuous deck barrier			3.20.9
	(d) Pulpit top rails no lower than upper lifelines			2 x 8ltr buckets stout construction with lanyard
3.12.3	(e) Openable upper rails able to be secured whilst racing			3.21.1
	(f) Pulpits & stanchions permanently installed			Marine magnetic compass permanently installed, non electric, and ship's compass deviation card
3.12.3	(g) Pulpits & stanchion bases inboard no more than greater of 5% of max beam or 150mm			3.21.2
	(h) Stanchion bases not outboard			Spare magnetic compass non electric
3.12.3	(i) Lifeline terminals may be aft of working deck if lifeline enclosure within working deck			3.22.1
	(j) If lifelines not fixed to bow pulpit, gap < 150mm			Minimum 2 halyards per mast
3.12.5	(k) Stanchions straight, vertical or angled not more than 10 degrees from 50mm above deck			3.23.1
	Lifeline height, spacing, number comply with table			Navigation lights carried complying with IRPCAS
3.12.6	(a) Lifelines uncoated stainless steel wire			3.23.2
	(b) Lifeline coating not moulded to wire			Not masked by sails or heeling
3.12.6	(d) Gap secured by lanyard 100mm or less Lanyard replaced annually			3.23.3
	(e) Strength lifeline system, wire size comply			Not mounted below deck level
3.12.6	(a) Lifelines uncoated stainless steel wire			3.23.4
	(b) Lifeline coating not moulded to wire			Reserve navigation lights; Independent of main power
3.12.6	(d) Gap secured by lanyard 100mm or less Lanyard replaced annually			3.23.5
	(e) Strength lifeline system, wire size comply			Spare bulbs except for multiple LED array lamps
3.12.6	(a) Lifelines uncoated stainless steel wire			3.24.3
	(b) Lifeline coating not moulded to wire			Inboard engine to SR 3.24.1, OR outboard engine with tanks, fuel supply all securely fastened
3.12.6	(d) Gap secured by lanyard 100mm or less Lanyard replaced annually			3.24.4
	(e) Strength lifeline system, wire size comply			Outboard motors provision for mounting, and raising Outboard motors mounted at all times
3.12.6	(a) Lifelines uncoated stainless steel wire			3.24.5
	(b) Lifeline coating not moulded to wire			Minimum speed, charging & fuel comply
3.12.6	(d) Gap secured by lanyard 100mm or less Lanyard replaced annually			3.24.6
	(e) Strength lifeline system, wire size comply			Separate starter battery
3.12.6	(a) Lifelines uncoated stainless steel wire			3.24.7
	(b) Lifeline coating not moulded to wire			Separate generators, if carried & permanently installed; covered; all exhaust, fuel supply & tank also permanently installed
3.12.6	(d) Gap secured by lanyard 100mm or less Lanyard replaced annually			3.24.8
	(e) Strength lifeline system, wire size comply			Fuel tank shut off valve/ cocks(s) if fuel can escape or siphoning possible
3.12.6	(a) Lifelines uncoated stainless steel wire			3.24.9
	(b) Lifeline coating not moulded to wire			
3.12.6	(d) Gap secured by lanyard 100mm or less Lanyard replaced annually			(a) Inboard petrol tanks permanently installed, metal, vented to open air, electrically grounded, filler position prevents fuel/vapour entering boat
	(e) Strength lifeline system, wire size comply			(b) Diesel tanks metal or other certified material
3.12.6	(a) Lifelines uncoated stainless steel wire			(c) Fuel lines comply
	(b) Lifeline coating not moulded to wire			(d) Outboard tanks secured on deck or ventilated compartment; manufacturer supplied or standards branded
3.12.6	(d) Gap secured by lanyard 100mm or less Lanyard replaced annually			(e) Petrol not below decks in portable containers
	(e) Strength lifeline system, wire size comply			(f) Flexible fuel tank not permitted.
3.12.6	(a) Lifelines uncoated stainless steel wire			3.25.1
	(b) Lifeline coating not moulded to wire			
3.12.6	(d) Gap secured by lanyard 100mm or less Lanyard replaced annually			i Permanently installed VHF transceiver
	(e) Strength lifeline system, wire size comply			(b) iii From 1/07/15, newly installed to be DSC capable

CATEGORY 3	MONOHULLS	For Offshore races across open water which is relatively protected or close to shorelines
DATE OF AUDIT ____ / ____ / ____	SAIL NO:	BOAT NAME:

4.07.9 FIRST AID KIT CONTENTS LIST

Paracetamol 500mg (eg Panadol) or Ibuprofen 200 mg (eg Nurofen) x 40	Band-aids or equivalent roll of bandaid x 20
Codeine 8mg + Paracetamol 500mg (eg Panadeine) x 40	Antiseptic skin solution 15ml (eg Betadine) x1
Soluble Aspirin (eg Disprin) x 20	Antiseptic cream with lignocaine HCL (eg Medcream) x 1
Butterfly or Steristrips (Strips of 5) x 5	Normal saline (for washing) - 250ml x 1
Disposable Gloves x 20	Sunscreen 30 + SPF - 250 ml x 1
Crepe bandages 75mm x 1.5m x 2	Travel/seasickness tablets (eg Avomine, Travacalm) x10
Triangular bandage x 1	Scissors, stainless steel x 1
Low absorbency non-adherent dressing (eg Melolin) x 10	CPR mask x 1 or face shields x 6

ADDITIONAL ITEMS, if any, REQUIRED BY NoR

END OF FORM